



Workshop Essentials 2025

















Winntec Workshop Essentials Contents

| 01 | Litting Equipment | | | UZ - 15 |
|-----------|------------------------------------|-------|------------------------------|----------------|
| UI. | >> Floor Jacks | 02 | » Air Hydraulic Jacks | 11 |
| | » Liftpads | 06 | >> Bottle Jacks | 12 |
| | » Long Chassis Jacks | 10 | » Air Bottle Jacks | 13 |
| | >> Forklift & Tractor Jack | 10 | >> Balloon Jacks | 14 |
| | | | | |
| | | | | |
| 02 | Wheel Handling Equi | pment | | 16 - 21 |
| 02. | Wheel Handling Equi » Smart Carts | pment | >> Wheel Assist & Wheel Lift | 16 - 21 |

| 07 | Workshop Equipment | | | 22 - 41 |
|-----|---------------------------|----|-----------------------|---------|
| 03. | >> Electrohydraulic Press | 24 | >> Engine Stand | 31 |
| | >> Hydraulic Press | 25 | >> Transmission Jack | 31 |
| | >> Vehicle Lifts | 28 | » Jack Stands | 34 |
| | >> Foldable Crane | 30 | >> Miscellaneous | 38 |
| | >> Battery Lift | 31 | | |
| 0/- | Jack the Mech | | | 40 - 41 |
| 04. | Detailing Seat | 42 | » Mobile Energy & Air | 40 |
| | >> Start Booster | 43 | | |



Reaching new **Heights**

This is who we are:

Winntec is a leading manufacturer, renowned developer, and global supplier of premium-quality, efficient, and reliable automotive workshop essentials. Our award-winning and patented Smart Carts, Wheel Lifts and Safergo have rocked the automotive industry.

We don't just manufacture automotive workshop essentials; we redefine them!

User-friendliness is at the heart of our design philosophy, with safety and comfort being amongst the top priorities. Our durable, high-quality products are crafted to meet the ever increasing demands of mechanics-all at competitive prices. Plus, our outstanding customer service ensures you have all the support you need.

As we look to the future, our goal is clear.

We recognize the unique challenges mechanics face, both in the workshop and on the road. With vehicle and component weights continuing to rise, we're committed to delivering cost-effective solutions for lifting, handling, and transporting that save time and minimize risk.

Winntec lifting products meet NEN-EN 1494:2001+A1:2008 standards and are perfectly serviceable, ensuring reliable, high-quality investments.

No rights can be derived from the contents of this folder. Images shown may differ from reality. Print and text errors reserved.

WE ARE PROUD TO BE THE DRIVING FORCE BEHIND:















WINNTEC HEADQUARTERS (NL)









Lifting Equipment

Floor Jacks

After we founded Winntec in 2002, we completely redesigned the hydraulic floor jack from the ground up.

The result was an innovative, operator-friendly, and serviceable design that blended the best of European and American features and functionality. We pioneered technologies like TURBO LIFT and 2-SPEED LOWERING, which began as unique features and are now standard on nearly all our jacks.

Today, we offer the most comprehensive range of hydraulic jacks in the industry, with capacities from 1.35 to 32T.

The majority of our jacks undergo rigorous testing, are third-party certified, and come with a straightforward 3-year hydraulic manufacturer's warranty. Alongside our heavy-duty workshop jacks, we also provide lightweight models designed for mobile use.

Quality, safety, and ease of use have always been, and will continue to be, at the core of our operations.

BMW selects the Y411350 for use in their mobile service vehicles The first lifting brand to offer 3 years hydraulic 2014 warranty Introduction of a wheel lifter that requires no oil, electricity, or air The sale of our 50,000th Smart Cart, dominating 2024 the industry Mercedes-Benz selects the Y411202, Y452330 & Y450350 for use in their mobile service vehicles



TURBO LIFT

Allows your jack to rise quickly with the use of the foot pedal



2-SPEED LOWERING

Enables your jack to lower slowly under load, yet fast without.



Floor Jack dimensions Values are in mm and kg unless stated otherwise.

| Model | Min. H. | Max. H. | Width | Length | Material | 112/1 | KG |
|---------|---------|---------|-------|--------|----------------|--------|---------|
| Y411350 | 80 | 375 | 236 | 501 | Aluminum | 1.35 T | 10 |
| M411355 | 90 | 360 | 247 | 481 | Aluminum/Steel | 1.5 T | 14 |
| Y411202 | 86 | 418 | 282 | 625 | Aluminum/Steel | 2 T | 22 |
| Y420222 | 75 | 500 | 350 | 705 | Steel | 2 T | 42 kg |
| Y420250 | 75 | 510 | 343 | 686 | Steel | 2 T | 32.5 kg |
| Y420330 | 120 | 450 | 344 | 618 | Steel | 3 TN | 31 kg |
| Y420333 | 76 | 503 | 346 | 672 | Steel | 3 T | 37 kg |
| Y420336 | 95 | 540 | 350 | 688 | Steel | 3.6 T | 38.5 kg |

Y411350 - Full Aluminum Jack 1.35T

This premium full aluminum jack is designed for effortless handling and robust performance. Featuring a thick, durable frame and a reinforced lift arm, it ensures reliability during heavy-duty tasks. Built-in bypass and overload valves offer added safety. The two-piece handle includes a quick-lock mechanism, making storage simple and hassle-free.

| Specifications | | | | | |
|-----------------------|--|--|--|--|--|
| Min. H. 80 mm | | | | | |
| Max. H. 375 mm | | | | | |
| Width 236 mm | | | | | |
| Length 501 mm | | | | | |
| 1.35 T | | | | | |
| 10 kg | | | | | |





Main Features

· Rubber saddle pad

• ONLY 10 KG!

Nvlon wheels



M411355 - Aluminum/Steel Jack 1.5T

High-performance aluminum/steel jack that combines portability with advanced functionality. It features powerful TURBO LIFT technology for rapid lifting and a 2-speed lowering mechanism that ensures smooth and precise control. Packaged in a sleek color box, it's the perfect blend of style, performance, and convenience, making it an ideal choice for both professionals and enthusiasts.

| Specifica | Specifications | | | | | |
|----------------------|----------------|--|--|--|--|--|
| Min. H. 90 mn | | | | | | |
| Max. H. | 360 mm | | | | | |
| Width | 247 mm | | | | | |
| Length | 481 mm | | | | | |
| 415/4 | 1.5 T | | | | | |
| 14 } | | | | | | |





Main Features

- 2-SPEED LOWERING
- TURBO LIFT
- · Rubber saddle pad





Y411202 - Aluminum/Steel Jack 2T

Combining durability and ease of use in a lightweight design. Built with a robust aluminum/steel construction, this jack features Turbo Lift technology, allowing for quick and effortless lifting and 2-speed lowering ensures smooth, controlled lowering for safe operation every time. A foot pedal provides hands-free convenience, while the PU wheels minimize noise and protect sensitive surfaces.

| Specifications | | | | | |
|-----------------------|--------------|--|--|--|--|
| Min. H. 86 mm | | | | | |
| Max. H. 418 mm | | | | | |
| Width | Width 282 mm | | | | |
| Length | 625 mm | | | | |
| 112/1 | 2 T | | | | |
| 22 kg | | | | | |





Main Features

- 2-SPEED LOWERING
- TURBO LIFT
- Foot pedalPU wheels
- Rubber saddle pad





Y420250 - Ultra Low Floor Jack 2T

This jack features an ultra-low profile design combined with TURBO LIFTER technology. It starts at just 75 mm and reaches an impressive maximum height of 510 mm. The PU wheels minimize noise and reduce the risk of damage to showroom floors. It comes with heat-treated chromed pump pistons and a chromed main ram. Like all our other jacks, it is equipped with cardan transmission.

| Specifications | | | | | |
|---------------------|--------|--|--|--|--|
| Min. H. 75 n | | | | | |
| Max. H. | 510 mm | | | | |
| Width | 343 mm | | | | |
| Length | 686 mm | | | | |
| 112/11 | 2 T | | | | |
| 32.5 kg | | | | | |
| | | | | | |





Main Features

- 2-SPEED LOWERING
- TURBO LIFT
- · Rubber saddle pad
- · PU wheels

Y420330 - Compact Floor Jack 3TN

Designed for efficiency and ease of use, featuring innovative noise-reducing PU wheels that provide smooth and quiet operation. Equipped with a rubber saddle pad to ensure a secure grip on the vehicle and to prevent damage. Featuring 2-speed lowering and Turbo Lift technology. The ram and pistons are chrome-plated for enhanced durability and longevity.

| Specifications | | | | | | |
|-----------------------|--|--|--|--|--|--|
| Min. H. 120 mm | | | | | | |
| Max. H. 450 mm | | | | | | |
| Width 344 mn | | | | | | |
| Length 618 mm | | | | | | |
| **** 3 TN | | | | | | |
| 31 kg | | | | | | |



Main Features

- 2-SPEED LOWERING
- TURBO LIFT
- · Rubber saddle pad
- PU wheels





Y420222 - Ultra Low Floor Jack with Integrated Jack Stand Function 2T

This ultra-low floor jack (75 mm) features an integrated jack stand function and a maximum lifting height of 500 mm. It includes hold-to-run control for added convenience. The PU wheels are designed to reduce noise and protect floors from damage. The saddle is covered with a rubber pad to prevent any harm to the underside of the chassis, while the handle is equipped with a bumper to safeguard the car from scratches.

| Specifications | | | | | |
|----------------------|--------------|--|--|--|--|
| Min. H. 75 mm | | | | | |
| Max. H. | 500 mm | | | | |
| Width | Width 350 mm | | | | |
| Length | 705 mm | | | | |
| 118/4 | 2 T | | | | |
| KG | 42 kg | | | | |



Main Features

- INTEGRATED JACKSTAND FUNCTION
- 2-SPEED LOWERING
- TURBO LIFT
- · Hard-chromed ram and pistons





Y420333 - Ultra Low Floor Jack 3T

"The ULTIMATE" floor jack combines an ultra-low profile with impressive high reach, making it ideal for low-clearance vehicles. It delivers powerful performance, while the advanced 2-Speed Lowering and Turbo Lift technologies ensure fast, efficient lifting and lowering. The noise-reducing PU wheels ensure smooth and quiet operation. The jack is equipped with a rubber saddle pad and a convenient foot pedal.

| Specifications | | | | | |
|----------------------|--------|--|--|--|--|
| Min. H. 76 mm | | | | | |
| Max. H. | 503 mm | | | | |
| Width 346 mm | | | | | |
| Length | 672 mm | | | | |
| 112/1 | 3 T | | | | |
| кс | 37 kg | | | | |



Main Features

- 2-SPEED LOWERING
- TURBO LIFT
- · Rubber saddle pad
- · PU wheels
- · Foot pedal





Y420336 - Low Floor Jack High Reach 3.6T

Powerful 3.6-ton jack designed for both low entry height and impressive 540 mm lifting capacity. It features advanced 2-Speed Lowering and Turbo Lift technologies for quick, efficient operation. The rubber grip and rubber pad provide added stability and protection, while the chrome-plated pistons ensure durability. Industrial-grade polyamide wheels deliver smooth, reliable performance. Additionally, the welded pump makes it a reliable tool for any heavy-duty lifting task.

| Specifications | | | | | |
|-----------------------|---------|--|--|--|--|
| Min. H. 95 mm | | | | | |
| Max. H. 540 mm | | | | | |
| Width 350 mm | | | | | |
| Length 687 mm | | | | | |
| 484 | 3.6 T | | | | |
| KG | 38.5 kg | | | | |



Main Features


- 2-SPEED LOWERING
- TURBO LIFT
- Rubber grip
- · Polyamide whee
- Rubber pad
- Welded pump





MAXIMUM





Our rigid liftpads ensure damage-free lifting, with the S and EV pads being ideal for cars that need an adapter.

Lifting Equipment Dedicated Liftpads





Lifting Adapters

safe lifting.

More and more vehicles, especially electric vehicles (EVs), require lifting adapters for

Winntec's Liftpads are designed to fit the majority of these adapters to ensure safe lifting and reduce the risk of damage.

Additionally, our pads are completely PFAS

Y490000 - Liftpad X

Provides safe lifting without damaging your vehicle, featuring an X-groove for precise alignment. Fully compatible with most floor jacks.

Perfect fit for: Y411202, Y420250, Y420303, Y420330, Y420333, Y420336.



Y490010EV - Liftpad EV

Designed for lifting vehicles that require an adapter, with built-in magnets on the bottom for a secure and stable hold.

Perfect fit for: Y411202, Y420250, Y420303, Y420330, Y420333, Y420336.





Y490020 - Liftpad S

Ensures safe lifting without damaging your vehicle, featuring an X-groove and an adapter slot for easy use with lifting adapters.

Perfect fit for: Y411350, Y420222 & M411355.







Liftpad dimensions Values are in mm and grams.

| Model | Α | В | С | D | E | F | G | KG |
|---------|-----|----|-------|----|-----|-----|-----|-----|
| Y490000 | 122 | 43 | 10/13 | 92 | 104 | 106 | 118 | 400 |
| Y490010 | 112 | 20 | ø 75 | 92 | 104 | 106 | 118 | 150 |
| Y490020 | 110 | 43 | 10/13 | 80 | - | - | 100 | 300 |

| C C | _ |
|-----|---|
| | 1 |
| | В |
| | _ |
| E | |
| F | |
| G | |
| _ | |

Y411350-42 - Fully Covering Saddle Pad

Perfect fit guaranteed with our: Y411350.



M411355-01 - Inlay Saddle Pad Yellow

Perfect fit guaranteed with our: M411355.



Y420250-34 - Inlay Saddle Pad

Perfect fit guaranteed with our: Y420250, Y420330 & Y420333.





Y420336-42 - Inlay Saddle Pad

Perfect fit guaranteed with our: Y420336.





Y411202-51 - Handle Bumper

Upgrade your jack today with our Heavy-Duty Handle Bumper. Designed to absorb impact and minimize wear, this bumper is a reliable solution for protecting your equipment and customer's vehicle.

Perfect fit guaranteed with our: Y411202, Y420250,

50 mm



Y420330 & Y420333.

Outer diameter:



Y411202-45 - Fully Covering Saddle Pad

Perfect fit guaranteed with our: Y411202, Y420250, Y420330 & Y420333.



We support & sponsor multiple racing teams, fueling their pursuit of excellence & driving product innovation.


Lifting Equipment Long Chassis Jacks


Long Chassis Jacks 2 - 10T

Our Long Chassis Jacks are designed for heavy-duty lifting, featuring foot pedals for quick elevation and ergonomically designed handles with a release button for gradual lowering. Additionally, these jacks are equipped with an automatic overload safety valve and durable swivel castors for easy maneuverability.

Long Chassis Jack dimensions Values are in mm and kg unless stated otherwise.

| Model | А | В | С | D | Е | 421 | КБ |
|---------|-----|-----|-----|-------|-------|------|-----|
| Y420200 | 138 | 800 | 396 | 1,310 | 1,285 | 2 T | 58 |
| Y420301 | 130 | 600 | 325 | 1,400 | 1,330 | 3 T | 65 |
| Y420500 | 150 | 680 | 366 | 1,505 | 1,345 | 5 T | 90 |
| Y421000 | 160 | 680 | 485 | 1,635 | 1,355 | 10 T | 145 |





Main Features

- ERGONOMIC HANDLE
- Foot pedal
- · Overload safety valve
- · Durable swivel castors





Lifting Equipment Forklift & Tractor Jack

Y454000 - Forklift & Tractor Jack 4/5T


Our forklift jack is equipped with dual lifting points (4/5T), 2-speed lowering, and a durable chrome-plated ram and pump piston. The extended lower arm is just 65mm, providing easy access under forklift trucks, while the 416mm upright piston is ideal for lifting tractors and farm machinery. It offers a hydraulic lift of 355mm on the forklift arm and 309mm on the upright piston. The jack also features a removable handle and a compact design.

Forklift Jack dimensions Values are in mm and kg unless stated otherwise.

| Model | Max. H. 1 | Max. H. 2 | Min. H. 1 | Min. H. 2 | Walt. | KG |
|---------|-----------|-----------|-----------|-----------|-------|----|
| Y454000 | 425 | 725 | 65 | 416 | 4/5 T | 45 |

Main Features

- 2-SPEED LOWERING
- · 2-Position lift pad
- · High-strength framework





Lifting Equipment Air Hydraulic Jacks


Y432024 - Single Stage Air Service Jack 24T


This single-stage air service jack delivers 24 tons of lifting power with premium hydraulic and pneumatic components. Designed for top performance at a competitive price, it allows safe air-powered lifting and lowering, eliminating the need for manual descent on heavy trucks. The Y432024 includes 3 extensions (20mm, 50mm, 100mm) and an 85mm extension screw. Heavy-duty wheels ensure durability.


Air Hydraulic Jack dimensions Values are in mm and kg unless stated otherwise.

| Model | Α | В | С | D | Ε | F | G | Way. | KG |
|---------|-----|-----|----|-----|-------|-----|-----|---------|----|
| Y432024 | 215 | 141 | 85 | 525 | 1,240 | 265 | 441 | 24 T | 40 |
| Y432032 | 150 | 73 | 66 | 480 | 1,300 | 290 | 289 | 32/16 T | 38 |









Y432032 - Telescopic Air Service Jack 32T

This dual-stage air service jack features a low entry height of just 150mm and a hard-chromed piston. With a 32/16 ton capacity and compact design, it's perfect for both workshop and roadside assistance. Air-controlled ascent and descent provide maximum safety. It comes with two extensions (45mm and 100mm).



Main Features

- HARD CHROMED PISTONS
- · Pneumatic descend
- · Dead-man control
- · Only 150mm min. height
- · Comes with 2 extensions



Main Features

- HARD CHROMED PISTON
- · Pneumatic descend
- · Dead-man control
- · Extension screw




CLEARANCE

MAXIMUM MOBILITY











GT260MM-EXT

Extension for the Y432032 that increases its reach by 260mm





Lifting Equipment

Bottle Jacks

Bottle Jacks 2-30T

 CHROMED PISTONS · Easy maintenance · Heat-treated saddle

Highly versatile and suitable for a wide range of applications, including pushing, bending, pressing, and straightening. Each model features a cast iron base, polished main ram, and a solid, chrome-plated pump linkage. Tested to meet the latest European standards, they offer overload protection and can be used in both horizontal and vertical positions.

All models, except the Y413000 and Y411000, come with a twist top for precise height adjustments.



Y411000 - 10T


The telescopic Y411000 features 2 extensions (45 mm and 6 mm), internally machined oil passages and smooth bearing surfaces, ensuring superior performance.





Bottle Jack dimensions Values are in mm and kg unless stated otherwise.

| Model | Base Plate | Min. H. | Lifting H. | Adjustable H. | Max. H. | W. W | KG |
|---------|------------|---------|------------|---------------|---------|------|------|
| Y410200 | 96 x 93 | 158 | 90 | 60 | 308 | 2 T | 2.3 |
| Y410400 | 112 x 104 | 180 | 110 | 60 | 350 | 4 T | 3.3 |
| Y410600 | 116 x 116 | 197 | 125 | 60 | 382 | 6 T | 4.4 |
| Y410800 | 120 x 120 | 205 | 125 | 60 | 390 | 8 T | 5.4 |
| Y411000 | 180 x 118 | 120 | 100 | - | 260 | 10 T | 6.4 |
| Y411200 | 140 x 135 | 214 | 125 | 60 | 399 | 12 T | 7.2 |
| Y411500 | 140 x 140 | 225 | 140 | 60 | 425 | 16 T | 8.3 |
| Y412000 | 155 x 140 | 244 | 145 | 60 | 449 | 20 T | 10.5 |
| Y412001 | 155 x 140 | 190 | 90 | 60 | 340 | 20 T | 9 |
| Y413000 | 175 x 160 | 285 | 180 | - | 465 | 30 T | 14.6 |



Y413000

Air Bottle Jacks

Highly versatile and suitable for a wide range of applications, including pushing, bending, pressing, and straightening. Each model features an air regulator, extension screw, specially heat-treated cylinder wall, chromed ram, and a welded base to ensure reliability. Filters prevent contaminates from entering the

Lifting Equipment

Air Bottle Jacks

Main Features

- WELDED BASE
- · Extension screw
- High speed air motor
- · Chromed ram

Y432021 - Low Profile Air Bottle Jack 20T

Designed to handle up to 20 tons with ease, it features a welded base that enhances stability and extends the service life of the unit. The jack is equipped with a chrome main ram and an aluminum air motor, ensuring exceptional durability and long-term performance. An integrated air filter and regulator, pre-connected to the hose, provide clean and precise operation for consistent results.



Y432020 - Air Bottle Jack 20T

Designed and built to handle the toughest jobs with unmatched durability and reliability. This air bottle jack features an air regulator, chrome ram, welded base, and robust return springs. They are designed to perform flawlessly under demanding conditions. Every unit is rigorously hand-tested before shipping, ensuring maximum reliability and consistent performance on every



Y432003 - Air Bottle Jack On Trolley 20T

The Y432020 Jack, mounted on a convenient trolley, is designed for effortless maneuverability and superior performance. Engineered to tackle the toughest jobs, it boasts unmatched durability and reliability. Key features include an air regulator, chrome ram, welded base, and heavy-duty return springs, ensuring flawless operation even in the most demanding conditions. Each unit undergoes rigorous hand-testing before shipping, guaranteeing maximum reliability and consistent results every time.



| Model | Base Plate | Min. H. | Max. H. | 42/4 | к |
|---------|------------|---------|---------|------|------|
| Y432021 | 180 x 115 | 148 | 260 | 20 T | 9 |
| Y432020 | 220 x 175 | 245 | 475 | 20 T | 16.5 |
| Y432003 | 300 x150 | 253 | 483 | 20 T | 26 |



Lifting Equipment Balloon Jacks

Balloon Jacks

Highly versatile and suitable for a wide range of applications, including pushing, bending, pressing, and straightening. Each model features an air regulator, extension screw, specially heat-treated cylinder wall, chromed ram, and a welded base to ensure reliability. Filters prevent contaminates from entering the air/hydraulic system.







Y422002 - Pneumatic Balloon Jack 2T

Lifts quickly and is easily positioned on a car lift. A safety valve prevents over-inflation, while the internal telescopic stabilizer (made from ASTM-513 steel) ensures stability.

Main Features

- PRECISE HEIGHT CONTROL
- IDEAL ON 4 POST LIFT
- INTERNAL TELESCOPIC STABILIZER
- · Safety valve
- · Low profile
- · 2-Stage





Exploring Winntechnology

In the second episode of Exploring WINNTEChnology, we dive into the unique features that set our balloon jacks apart.








Y422012 - Pneumatic Balloon Jack 2T

Our Y422002 equipped with a handle and wheels for easy positioning under the vehicle.


Main Features

- PRECISE HEIGHT CONTROL
- HIGHLY MANEUVERABLE
- INTERNAL TELESCOPIC STABILIZER
- · Safety valve
- · Low profile
- 2-Stage





| Model | А | A^1 | В | B1 | D | E | 42/4 | KG |
|---------|-----|-------|-----|-----|-------|-----|------|----|
| Y422002 | 300 | 360 | 125 | 185 | 400 | - | 2 T | 15 |
| Y422012 | 300 | 360 | 125 | 185 | 1,000 | 280 | 2 T | 16 |





Lifting solutions for every application, whether in the shop or for roadside assistance.



Winntec Smart Carts are the #1 choice in motorsports for their durability, comfort and speed!

Wheel Handling Equipment

For cars and vans













Y471147HD Classic - Smart Cart Ø 76 cm

Our lightweight, high-capacity Classic Smart Cart features patented LOADSHIFT™ technology and is equipped with a unique push-slide-secure automatic locking system and made from durable powder-coated steel. It comes with maintenance-free foam-filled tires that leave no traces.

Main Features

- REQUIRES 3x LESS EFFORT TO TILT/LIFT
- · Auto open/close grippers
- · Handles tires and wheel assemblies



to handle larger loads with ease. It boasts an integrated kick pedal, redesigned stainless steel arms and a bracket set for carrying a Smart Disc.

Main Features

REQUIRES 3x LESS EFFORT TO TILT/LIFT

Y471148HD Dominator - Smart Cart Ø 83 cm

After changing the industry with our Classic Smart Cart, domination is next:

The new Dominator, featuring patented **LOADSHIFT**™ technology, is designed

- 3+7 YEARS WARRANTY (upon activation)
- Solid rubber tires with cast alu rims
- · Spring-operated integrated kick pedal
- Adjustable top plate with rubber grips
- · Comes with brackets for a Smart Disc*





Product dimensions Values are in mm and kg unless stated otherwise.

Y4711SPP - Push Pull Ext Kit

OPTIONAL retro-fit extender to increase the

| Model | Height | Width | Depth | Reach Ø | May t | к |
|---------|--------|-------|-------|----------|-------|------|
| Y471147 | 1,385 | 610 | 695 | up to 76 | 200 | 20.5 |
| Y471148 | 1,385 | 610 | 695 | up to 83 | 220 | 25 |

Y471147HD-PW - Wheel Kit

OPTIONAL retrofit kit to replace the wheels of the carrying capacity of your Smart Cart, while the Y471147HD with those of the Y471148HD. The kit Push-Pull lever ensures a quick release of the load. includes 2 wheels, 2 axle caps, and 2 bushings.





Y471148EXT - Extender Kit

OPTIONAL bolt-on/off retro-fit extender with rubber grips to increase the carrying capacity of your DOMINATOR. Easy installation and removal.



Y471123 - Smart Disc

Our second generation Smart Disc ensures greater mobility and flexibility, as loads of up to 160 kg can be moved effortlessly. Perfect for showcasing tire sets in the showroom.

Additionally, the Smart Disc can be paired with our Y471147HD and Y471148HD Smart Carts to enhance their swiftness, efficiency, and ease of use!





| Model | Ø | Height | Walt. | к |
|---------|-----|--------|-------|-----|
| Y471123 | 680 | 85 | 160 | 3.5 |

Y472270 - Wheel Assist ERGO+

The Winntec Wheel Assist is a patented standalone workshop tool that uses powerful gas springs, enabling technicians to quickly and easily remove and replace wheels while maintaining an ergonomic position.



$\begin{tabular}{ll} \textbf{Product dimensions} & \textit{Values are in mm and kg unless stated otherwise.} \end{tabular}$

| Model | Height | Width | Depth | 112/1 | KG |
|---------|--------|-------|-------|-------|----|
| Y472270 | 1,800 | 685 | 720 | 45 | 42 |
| Y472280 | 1,730 | 930 | 520 | 70 | 45 |

Y472280 - Wheel Lift NXT

Swiftly lift and lower wheel assemblies from floor to shoulder height while maintaining an ergonomic position. Patents pending. Operates with the majority of premium cordless drill brands

Distance between adjustable rollers:

Minimal: A. 452 mm Center-to-center: A. 500 mm B. 372 mm

Main Features

 NO HOSES · Floor to shoulder height · Precise positioning

· Minimal footprint





* Cordless drill not included

Wheel Handling EquipmentFor trucks

Y471105 - Wheel Dolly

Quickly and efficiently remove wheel assemblies. Its ergonomic design reduces the risk of back strain injuries. Equipped with adjustable extended rollers and rubber wheels with a steel core.

Main Features

- QUICK DETACH HANDLE
- Extended rollers 290 mm
- Steel core rubber wheels



Y471106 - Hydraulic Wheel Dolly

This lightweight, portable dolly features a hydraulic unit, enabling the operator to work in close proximity to the vehicle, making it ideal for roadside service. Its shock-absorbing casters ensure a smooth ride.

Main Features

- CARRY HANDLE & BELT
- Maximum mobility
- Fast positioning







 $\begin{tabular}{ll} \textbf{Product dimensions} & \textit{Values are in mm and kg unless stated otherwise.} \end{tabular}$

| Model | Length | Width | Height | 112/4 | KG |
|---------|--------|-------|---------|-------|----|
| Y471105 | 1,150 | 700 | 250/755 | 220 | 15 |
| Y471106 | 900 | 450 | 310 | 160 | 29 |







Our Smart Carts and Wheel Lifts form a strong duo. Time savings guaranteed!



Our welded-frame presses are precision-engineered to handle a wide range of demanding tasks.

Workshop Equipment

Electric Industrial Presses

Y461720E - Press 20T

• 2-SPEED HAND PUMP

· Movable cylinder (left-right) · Foot and/or hand operation

Electrohydraulic Industrial Presses 20 - 50T

These feature a 2-speed hand pump, movable cylinder, and can be operated by both foot and hand for maximum convenience. Built with a durable welded frame, they excel in pressing, bending, bonding, and straightening. Perfect for heavy-duty tasks, such as the removal and installation of universal joints, bearings, pulleys, and wrist pins. Each press includes two precision V-blocks for accurate positioning.

- **4** EASIER OPERATION
- **4** AUTOMATION & INTEGRATION
- Faster response times
- Less maintenance
- 4 Reduced risk of leaks
- Improved control higher precision
 - **Y461730E Press 30T**
 - 2-SPEED HAND PUMP
 - Movable cylinder (left-right)
 - · Foot and/or hand operation



- 2-SPEED HAND PUMP • Movable cylinder (left-right)

Y461750E - Press 50T

· Foot and/or hand operation





Press dimensions Values are in mm & kg unless stated otherwise.

| Model | Height | Depth | Width | ٧ | Power | 12/1 | KG |
|----------|--------|-------|-------|-----|-------|------|-----|
| Y461516 | 1,015 | 134 | 678 | - | - | 15 T | 57 |
| Y461520 | 1,830 | 540 | 850 | - | - | 20 T | 101 |
| Y461533 | 1,850 | 540 | 840 | | - | 30 T | 137 |
| Y461555 | 1,850 | 650 | 1,080 | - | - | 50 T | 244 |
| Y461720E | 1,830 | 540 | 990 | 230 | 500 W | 20 T | 116 |
| Y461730E | 1,850 | 540 | 990 | 230 | 500 W | 30 T | 152 |
| Y461750E | 1,850 | 650 | 1,245 | 230 | 500 W | 50 T | 250 |

Workshop Equipment

Industrial Presses

Industrial Presses 15 - 50T

Our welded-frame presses are expertly designed to handle a variety of tasks, including pressing, bending, bonding, and straightening. They are essential for the removal and installation of universal joints, bearings, pulleys, and wrist pins. Each press is equipped with two V-blocks for easy and secure positioning, a 2-speed hand pump for efficient operation, and a movable cylinder adjustable from left to right for enhanced flexibility and convenience.

Y461516 - Bench Top Press 15T

Our Bench Top Press combines power, precision, and convenience in a compact design. This space-saving press is perfect for workbench use, delivering exceptional reliability for a variety of applications. Whether you're working on small components or intricate tasks, the press offers the performance and durability professionals expect, making it a reliable choice for garages, workshops, and industrial settings.

- BENCH MODEL
- 2-SPEED HAND PUMP
- MOVABLE CYLINDER (LEFT-RIGHT)

Y461533-PS

Punch Set



Y4615XX-PC

Protective Cover



Y461520 - Press 20T

• 2-SPEED HAND PUMP



Y461533 - Press 30T

- PNEUMATIC FOOT OPERATION
- 2-SPEED HAND PUMP
- MOVABLE CYLINDER (LEFT-RIGHT)



Y461555 - Press 50T

- PNEUMATIC FOOT OPERATION
- 2-SPEED HAND PUMP
- MOVABLE CYLINDER (LEFT-RIGHT)





Our extensive range is generally ergonomically designed and engineered to reduce injury risk.

Workshop Equipment Vehicle Lifts

Y475051 - IN-SYNCH2 2.5T

Easy to maneuver and offering open undercarriage access, it features quick-connect fittings for rapid (dis-)assembly and automatic remote release safety. Synchronized lifting is ensured by our patented valve blocks.

Main Features

- OPEN UNDERCARRIAGE ACCESS
- · Highly maneuverable
- · Lifts cars, vans and SUVs






Y475052 - RAZZ01 2.5T

This versatile mini lift, with a 2,500 kg weight capacity, uses an industrial air-hydraulic foot pump for smooth lifting of cars, vans and SUVs. Equipped with a mechanical safety lock and check valve, it ensures secure operation.

Main Features

- · Lifts cars, vans and SUVs
- · Mechanical safety lock





| Model | Min. H. | Max. H. | Width | Length | Pump | Inlet P. | May t | KG |
|---------|---------|---------|-------|-------------|---------|------------|-------|----|
| Y475051 | 85 | 455 | 300 | 1,800 | 350 Bar | 7 - 10 Bar | 2.5 T | 95 |
| Y475052 | 110 | 630 | 400 | 1,120-1,620 | 700 Bar | 7 - 10 Bar | 2.5 T | 89 |







Y475400 - Ultra Low Scissor Lift 3.2T

This lift features four synchronous cylinders for smooth, synchronized lifting. Floor fixation is optional. Limit devices enhance cylinder durability and ensure operator safety. The load-bearing ramp extends the platform to 2,000mm, making it ideal for SUVs and commercial vehicles. The anti-slip patterned platforms are treated for superior grip, corrosion resistance, and long-lasting durability. The integrated PLC features a self-testing function, offering fault diagnosis and ensuring safe voltage.

Main Features

- LOAD-BEARING RAMP
- Automatic balancing



Y475054 - Ultra Low Scissor Lift 3.5T

This lift features four synchronous cylinders for smooth, synchronized lifting. Floor fixation is optional, and mobility tools are included for easy relocation. Limit devices enhance cylinder durability and ensure operator safety. The load-bearing ramp extends the platform to 2,114mm, making it ideal for SUVs and commercial vehicles. The anti-slip patterned platforms are treated for superior grip, corrosion resistance, and long-lasting durability.

Main Features

- LOAD-BEARING RAMP
- · Automatic balancing



Product dimensions Values are in mm and kg unless stated otherwise.

| Model | Min. H. | Max. H. | Width | Length | Inlet P. | Frequency | Voltage | Motor Power | 1121 | KG |
|---------|---------|---------|-------------|---------------|-----------|-----------|---------|-------------|-------|-----|
| Y475400 | 105 | 1,900 | 585 / 2,020 | 1,460 / 2,000 | 6 - 8 Bar | 50 Hz | 400 V | 2.2 kW | 3,200 | 810 |
| Y475054 | 105 | 1,000 | 530 / 2,010 | 1,500 / 2,114 | 6 - 8 Bar | 50 Hz | 230 V | 2.2 kW | 3,500 | 690 |

Workshop Equipment

Gearbox, Battery & Engine Service

Y440104 - Foldable Crane 1T


This CE certified crane is designed to lift heavy vehicle parts like engines and transmissions, with three lifting arm positions (1,000 kg, 750 kg and 500 kg) for flexibility. It features foldable legs for easy storage, a dual-speed hydraulic pump that reduces strokes by half, and durable wheels. Safety is ensured with a "dead man" safety mechanism and overload valve.

$\begin{tabular}{ll} \pmb{Crane \ dimensions} & \textit{Values are in mm and kg unless stated otherwise.} \end{tabular}$

| Y440104 | | | | | | |
|---------|-------|---------|-------|--|--|--|
| P1 | 1,000 | H1 min. | 334 | | | |
| P2 | 750 | H2 min. | 214 | | | |
| Р3 | 500 | H3 min. | 94 | | | |
| А | 1,405 | H1 max. | 2,120 | | | |
| В | 80 | H2 max. | 2,210 | | | |
| С | 1,499 | H3 max. | 2,300 | | | |
| D | 1,009 | 112/4 | 1,000 | | | |
| E | 125 | KG | 74 | | | |

Main Features

- THREE LIFTING ARM POSITIONS
- DEAD MAN'S CONTROL
- · Foldable legs
- · Dual-speed hydraulic pump







Y475060 - Battery Lift 1.5T

Precise and efficient handling of heavy batteries. The upper platform features flexible tilt adjustment for easy positioning, while the lower platform slides in all directions for perfect alignment. Equipped with auto-lock protection, 8 rubber pads, anti-slip fasteners, and 2-speed lowering. This lift is an essential tool for any battery replacement or maintenance task.

Main Features

- SUPPORTS HEAVY LOADS
- · Flexible tilt adjustment
- 360-Degree sliding base
- · Enhanced safety features

Product dimensions Values are in mm and kg unless stated otherwise.

| Model | Min. H. | Max. H. | Width | Length | Pump | Inlet P. | 12/4 | KG |
|---------|---------|---------|-------|--------|---------|----------|-------|-----|
| Y475060 | 800 | 1,800 | 800 | 1,566 | 700 Bar | 8 Bar | 1,500 | 450 |

Y450102 - Engine Stand 450KG

Easily position and support your engine during repairs or maintenance. The adjustable arms ensure a perfect fit for various engine sizes. With the ability to rotate 360° using the handle, you can easily access all parts of the engine. A locking pin securely holds the stand in place at any of the 8 positions.

Product dimensions Values are in mm and kg unless stated otherwise.

| Model | Height | Width | Length | 42/1 | KG |
|---------|--------|-------|--------|------|----|
| Y450102 | 860 | 750 | 760 | 450 | 19 |

Main Features

- LOCKABLE IN 8 POSITIONS
- · Stable base
- Adjustable arms
- · Rotates 360° with handle

Y451555 - Transmission Jack 550KG

Its superior stability and efficient pump system ensure a fast and precise approach. Suitable for installing and dismantling gearboxes, engines & couplings. For use in pits and underneath elevated vehicles.

Product dimensions Values are in mm and kg unless stated otherwise.

| Model | Min. H. | Max. H. | Width | Length | 424 | KG |
|---------|---------|---------|-------|--------|-----|----|
| Y451555 | 1,171 | 1,989 | 573 | 542 | 550 | 31 |
| A D A P | - | - | 303 | 485 | - | 11 |

Main Features

- HOLD-TO-RUN CONTROL
- · Wide base with swivel wheels
- · Foam block to protect vehicle

Y451555ADAP

Adapter with adjustable arms and 360° rotatable handle. The locking pin secures in any of the 8











We select premium components, maintain strict quality control, and provide a 3-year hydraulic warranty.

Workshop Equipment

Jack Stands

Y450301 - Jack Stand 3T

- RATCHET TYPE
- AUTOMATIC LOCKING













• PIN TYPE

• LARGE PU SUPPORT PAD



Y451600 - Jack Stand 6T

RATCHET TYPE

AUTOMATIC LOCKING

· Carrying handle



Y452600 - Jack Stand 6T



Y452330 - Jack Stand 3T

Our **premium**, toughest jack stand is designed for maximum stability, featuring a large 310 mm base and extra-large foot pads. It is equipped with a durable, 100 mm diameter, replaceable PU saddle pad. The jack stand features a pin-type design and is TÜV and GS certified. Its robot-welded construction ensures exceptional durability.



Y450350 - Fast Lock Jack Block 3.5T

This innovative device replaces your jack stand.

With an adjustable height range of 217 mm to 352 mm, it is suitable for a variety of jacks and vehicle sizes. Easy to install, featuring a spring mechanism for smooth operation, and a safety pin for added security.









Y451205 - Low Profile Jack Stand SET 12T

This low-profile jack stand features a handle and wheels for easy positioning. The pin-type support column adjusts to five height positions.

- PIN TYPE
- SOLD AS A PAIR
- Low profile handle
- · Nylon wheels



Y452205 - Low Profile Jack Stand SET 22T

This heavy-duty, welded jack stand set features wheels and a detachable handle. The multi-angle handle sockets allow for easy storage and safe positioning under the vehicle.

- SOLD AS A PAIR
- Low profile handle
- Nylon wheels



Y451206 - High Reach Jack Stand 12T

This heavy-duty, high-reach welded jack stand features a detachable handle, multi-angle handle socket, and wheels for easy positioning under the vehicle.

The pin-type support column adjusts to various height positions, reaching up to 971 mm, making it ideal for tire service and general trailer support jobs. Sold individually.

- PIN TYPE
- SOLD INDIVIDUALLY
- · Low profile handle
- · Nylon wheels



Jack Stand dimensions Values are in mm and kg unless stated otherwise.

| Model | Min. H. | Max. H. | Width | Length | Ø | 12/4 | KG |
|---------|---------|---------|-------|--------|-----|-------|-----|
| Y450301 | 305 | 450 | 185 | 209 | - | 3 T | 7 |
| Y451600 | 395 | 625 | 263 | 293 | - | 6 T | 14 |
| Y452300 | 322 | 465 | - | - | 254 | 3 T | 5 |
| Y452600 | 404 | 604 | - | - | 341 | 6 T | 11 |
| Y452330 | 300 | 451 | - | - | 310 | 3 T | 9 |
| Y450350 | 217 | 352 | 40 | 90 | - | 3.5 T | 1.5 |
| Y451205 | 302 | 450 | 280 | 220 | - | 12 T | 20 |
| Y452205 | 402 | 575 | 333 | 280 | - | 22 T | 42 |
| Y451206 | 601 | 971 | 423 | 370 | - | 12 T | 29 |











Our jack stands provide the perfect support, ensuring safety and stability after lifting your vehicle.

Workshop Equipment

Miscellaneous

Y444000/Y444100 - Collision Repair Set 4/10T

Both the 4T (Y444000) and 10T (Y441000) models feature solid blow-molded cases, chrome-plated rams and pistons, and safety valves to prevent overloading. Their heavy-gauge snap-together pipework and cast attachments are compatible with most leading brands of body repair equipment.

Supplied with the following parts:

Single Speed Hand Pump • Cylinder (100mm stroke Y444000 - 150mm stroke Y444100) • Hose • Ram Flat Base • Spreader • 100mm Extension Tube • 150mm Extension Tube • 300mm Extension Tube • 400mm Extension Tube • Tube Coupling • Ram Toe • Wedge Head • Serrated Saddle • Flex Head • Plunger Toe • 90 Degrees Wedge Head • Storage Case

Main Features

- QUICK LOCK FOR EASY (DIS-)ASSEMBLY
- · Spring guards at hose end
- · Thick-walled extension tubes





| Model | Cylinder | Na It | KG |
|---------|----------|-------|----|
| Y444000 | 100 | 4 T | 17 |
| Y444100 | 150 | 10 T | 31 |

Y471180 - Wheel Removal Kit 10T

This kit addresses one of the most dangerous tasks in the tire service industry: wheel removal. Alloy and lightweight steel wheels often become frozen or glued to the vehicle.

This ready-to-use kit includes a case, cylinder, pump, hose, and a variety of adapters to accommodate different space constraints between the wheel and chassis. With 10 tons of hydraulic power and manual control via the foot pump, it allows for safe and efficient removal of oxidized wheels off the vehicle.

Main Features

- ALL-IN-ONE SOLUTION
- · Foot operated
- · Metal case



Kit dimensions Values are in mm and kg unless stated otherwise

| Model | Height | Width | Depth | 424 | KG |
|---------|--------|-------|-------|------|----|
| Y471180 | 150* | 480* | 235* | 10 T | 15 |

* Box Dimensions

Workshop Equipment Miscellaneous

Y471150 - Air Hydraulic Pump 1600cc

This tool is compatible with various rams, presses, and hydraulic tools operating up to 700 bar (10,000 psi). It features an air exhaust muffler for quiet operation and is housed in durable aluminum. The two-stage release mechanism allows for pump, hold, or release functions controlled by the pedal.

Air inlet: Hydraulic outlet: Working pressure: 6-10 bar



Y4781155 - Single Acting 2-Speed 900cc

Lightweight, high-flow industrial pump with a corrosion-resistant enamel finish, a compact design for easy storage and transport, and minimal operator fatigue. An internal pressure relief valve prevents overloads.

Industrial 3/8-18NPT outlet. Weight: 6.8 kg



Y471120 - Bead Breaker 5T

This tool fits 2-5-10 hole buds (single, double, triple-piece) and 7.50x16 tubeless tires/rims. It includes three claws, a 120mm working range, and a self-retracting design with a durable, anti-corrosive finish



Y478205 - Hose Assy. 2.5m

Compatible with Y471150 and Y471120.



Y490033 - Lunch Bag

- WARMING/COOLING
- · Compact size




Y491110 - Gloves L/XL

Sturdy gloves with protectors for extra safety.

Main Features

- IMPACT PROTECTION
- · Slip free silicone grip
- · Double stitched





Y491310 - Gloves L/XL

Perfect for jobs that demand a 'fine touch'.

Main Features

- FINE TOUCH
- Anti Slip
- · Breathable stretch
- · Abrasion resistant
- · Terrycloth thumb · Touch screen proof



Y490022 - Backpack

- · WATERPROOF FLOATS ON WATER · Extra spacious
























Winntec JTM Series JACK THE MECH

Designed for the pro - available to all

Winntec's Jack The Mech products are renowned for their high quality and durable construction. They are user-friendly and adaptable to individuals with varying levels of experience, making them a reliable choice for both professionals and enthusiasts.

Launched in 2022, 20 years after the founding of Winntec, the Jack The Mech range is specifically designed to cater to both home tinkerers and professionals.



This 12/24V start booster delivers a powerful 10,000A capacity, making it an indispensable tool for roadside service professionals. Engineered for reliability and efficiency, it features advanced clamp sensors that proactively alert users to resistance issues before initiating a start, ensuring safety and optimal performance.

Main Features

- START BOOSTER 10,000A 12V / 5,000A 24V
- · Multifunctional LED light
- · Multiple safety functions integrated

JTM200010 - Mobile Energy & Air

This versatile mobile battery booster is an essential tool for a variety of applications, including boats, motorhomes, and cars, as well as for everyday use in workshops, showrooms, and parking lots. It provides powerful jump-starting power and features a compressor with automatic start-stop functionality. The integrated power bank keeps your devices charged, while the multi-functional LED light enhances visibility in any condition.

Main Features

- START BOOSTER 2,000 A
- COMPRESSOR Auto-start-stop, 10 bar / 145 PSI
- POWER BANK High-Capacity 55.5 Wh
- LED Light Multifunctional











JTM400000 - Detailing seat

This sturdy workshop seat features a durable carbon steel inner frame and convenient onboard storage. The premium swivel casters - two of which are lockable - ensure mobility and stability. Its ergonomic cradle-style seating at a comfortable height is perfect for detailing, painting, repairing and polishing.

| Model | Size | KG |
|-----------|--------------------|---------|
| JTM101224 | 448 x 143 x 435 mm | 10.5 kg |
| JTM200010 | 280 x 180 x 135 mm | 2.5 kg |
| JTM400000 | 590 x 280 x 332 mm | 5 ka |

Main Features

- CARBON STEEL FRAMING
- · Swivel casters with 2 locks
- · Onboard storage


















RELEASE THE POWER INSIDE

